IQ8Alarm Plus IP 56 base, white

Part-No.: 806201

Common technical data	
Type of protection	IP 56
Color	white, similar to RAL 9010
Cable entry	Has breakthrough inputs for M20 cable glands (optional)

Features:

- Completely loop powered alarm device
- Powered loop compatible
- Low power consumption
- Up to 64 alarm devices for each powered loop
- Each alarm device has built-in isolator
- Synchronous trigger
- EN 54-23 compliant
- W category
- Signal range up to 8.0 m room width for wall mounting
- square signal range/ room size configurable via tools 8000
- EN 54-3 compliant
- High acoustic pressure
- Volume programmable in 8 steps via tools 8000
- 20 different signaling tones, including DIN tone
- Multilingual speech alarm in 5 different languages
- Alarm signaling, evacuation, and test alarm can each be programmed in different languages
- Speech alarm, 5 pre-programmed alarm texts and other country-typical alarm signals
- Tones can be used for other purposes in addition to warning of fire, making the device ideal for use in schools etc.
- Soft start option, ideal for hospitals and nursing homes
- Special variant with individual combination of up to 5 languages available
- Special variant with individual texts and/or sounds available

Subject to change without notice! © 2025 Honeywell International Inc.

Novar GmbH a Honeywell Company
Forumstr. 30 41468 Neuss
Phone: +49 2131 40615 600
Faximile: +49 2131 40615 606
www.esser-systems.com
esser-systems@honeywell.com